

FU52



Surface Downlight FU52

	UGR<19	CRI>80
Build-in power supply	IP20	Square/Round

- **Professional Optics**

Good quality COB chip, good color rendering.

- **Anti-glare**



UGR<19, 10W<UGR<16

- **Seamless appearance**

Integrated ADC12 aluminum die-cast shell, matt color and seamless appearance, delicate and fashion.

- **Application**

Offices, shopping mall, clothing shops



FU52 10W Round/Square

Item code	Product description	Pcs/ Carton
N03C4-0153	Olot LED-DL-FU52 WH-RD Surf10W3000K45°	24
N03C4-0154	Olot LED-DL-FU52 WH-RD Surf10W4000K45°	24
N03C4-0155	Olot LED-DL-FU52 WH-RD Surf10W5000K45°	24
N03C4-0162	Olot LED-DL-FU52 BK-RD Surf10W3000K45°	24
N03C4-0163	Olot LED-DL-FU52 BK-RD Surf10W4000K45°	24
N03C4-0164	Olot LED-DL-FU52 BK-RD Surf10W5000K45°	24
N03C4-0171	Olot LED-DL-FU52 WH-SQ Surf10W3000K45°	24
N03C4-0172	Olot LED-DL-FU52 WH-SQ Surf10W4000K45°	24
N03C4-0173	Olot LED-DL-FU52 WH-SQ Surf10W5000K45°	24
N03C4-0180	Olot LED-DL-FU52 BK-SQ Surf10W3000K45°	24
N03C4-0181	Olot LED-DL-FU52 BK-SQ Surf10W4000K45°	24
N03C4-0182	Olot LED-DL-FU52 BK-SQ Surf10W5000K45°	24

Installation

Surface RD: Round SQ: Square


IP

IP20


Parameter

Power: 10W Voltage: 220V
 Luminaire light output: 95lm (Cold white) CRI: >80
 Service life: 40000h Finishes: White/Black
 Color temperature 3000K/4000K/5000K WH: white BK: black
 PF & harmonic meet IEC61000-3-2.

Photometry



45°			
h(m)	d(m)	Ev	E _{max}
2	1.5	99.5	286.7
3	2.4	44.2	127.4
4	3.2	24.9	71.7
5	3.8	15.9	45.9



FU52 18W Round/Square

Item code	Product description	Pcs/ Carton
N03C4-0156	Olot LED-DL-FU52 WH-RD Surf18W3000K45°	18
N03C4-0157	Olot LED-DL-FU52 WH-RD Surf18W4000K45°	18
N03C4-0158	Olot LED-DL-FU52 WH-RD Surf18W5000K45°	18
N03C4-0165	Olot LED-DL-FU52 BK-RD Surf18W3000K45°	18
N03C4-0166	Olot LED-DL-FU52 BK-RD Surf18W4000K45°	18
N03C4-0167	Olot LED-DL-FU52 BK-RD Surf18W5000K45°	18
N03C4-0174	Olot LED-DL-FU52 WH-SQ Surf18W3000K45°	18
N03C4-0175	Olot LED-DL-FU52 WH-SQ Surf18W4000K45°	18
N03C4-0176	Olot LED-DL-FU52 WH-SQ Surf18W5000K45°	18
N03C4-0183	Olot LED-DL-FU52 BK-SQ Surf18W3000K45°	18
N03C4-0184	Olot LED-DL-FU52 BK-SQ Surf18W4000K45°	18
N03C4-0185	Olot LED-DL-FU52 BK-SQ Surf18W5000K45°	18

Installation

Surface RD: Round SQ: Square


IP

IP20


Parameter

Power: 18W Voltage: 220V
 Luminaire light output: 1710lm (Cold white) CRI: >80
 Service life: 40000h Finishes: White/Black
 Color temperature 3000K/4000K/5000K WH: white BK: black
 PF & harmonic meet IEC61000-3-2.

Photometry



45°			
h(m)	d(m)	Ev	E _{max}
2	1.5	251.4	666.7
3	2.4	111.7	296.3
4	3.2	62.8	166.7
5	3.8	40.2	106.7



FU52 30W Round

Item code	Product description	Pcs/Carton
N03C4-0159	Olot LED-DL-FU52 WH-RD Surf 30W3000K45°	12
N03C4-0160	Olot LED-DL-FU52 WH-RD Surf 30W4000K45°	12
N03C4-0161	Olot LED-DL-FU52 WH-RD Surf 30W5000K45°	12
N03C4-0168	Olot LED-DL-FU52 BK-RD Surf 30W3000K45°	12
N03C4-0169	Olot LED-DL-FU52 BK-RD Surf 30W4000K45°	12
N03C4-0170	Olot LED-DL-FU52 BK-RD Surf 30W5000K45°	12

Installation

Surface RD: Round


IP

IP20

Parameter

Power: 30W Voltage: 220V
 Luminaire light output: 2642 lm CRI: >80
 Service life: 40000h Finishes: White/Black
 Color temperature 3000K/4000K/5000K WH: white BK: black
 PF & harmonic meet IEC61000-3-2.

Photometry



45°			
h(m)	d(m)	Ev	E _{max}
2	1.5	346.5	954.6
3	2.4	153.9	424.3
4	3.2	86.6	238.7
5	3.8	55.4	152.7

